

Product Datasheet

15 Plafo>The LED Plafo Outdoor Round

67280AN/AN/W



24W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	300mm 78mm
Physical Specification	
Item Group	15 Plafo
Family	The LED Plafo Outdoor Round

Order Code

Colour

Material

Diffuser Material

Shape

67280AN/AN/W

Anthracite

Plastic

PC

Circular

Height	83mm
Diameter	300mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes



Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	38V
Power(Watts)	22,8W
IP Rating	IP65
Light Source	LED built in

LED Type

LED Brand	Epistar
LED Number	121
F Mark	F
Gear	
Gear Type	Led Driver

SMD 2835



Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15,6-26W
Power Factor	0,9
Constant Current	Yes
600mA	26-43,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise

Illumination Data


Colour Temperature	3000K
Lumen Output	1440lm
Light Efficiency	60lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	30,5cm
Box Width	30,5cm
Box Height	8,5cm

Box Weight	1,2Kg
Pcs/Carton	10
Barcode	5291889043331
HS Code	9405104090





Certification & Warranty 2 Years Warranty 2 Years Weee Directive Yes

switch to one light!



