



## **Product Datasheet**

#### 15 Plafo>The LED Plafo Outdoor Round

### 67280N/W/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











#### Downloads









#### Dimensions




#### **Physical Specification**

| Item Group        | 15 Plafo                    |
|-------------------|-----------------------------|
| Family            | The LED Plafo Outdoor Round |
| Order Code        | 67280N/W/W                  |
| Colour            | White                       |
| Material          | Plastic                     |
| Diffuser Material | PC                          |
| Shape             | Circular                    |
| Height            | 75mm                        |
| Diameter          | 260mm                       |
| Surface Ceiling   | Yes                         |
| Indoor            | Yes                         |
| Outdoor           | Yes                         |

| Adjustable                 | No               |
|----------------------------|------------------|
| IK Rating                  | 8                |
|                            |                  |
| Electrical Characteristics |                  |
| 0.00                       | De ille le       |
| Gear                       | Built In         |
| Fitting + Driver           |                  |
| Input Voltage              | 220-240V         |
| 50 Hz                      | Yes              |
| 60 Hz                      | Yes              |
| Safety Class               |                  |
| Power(Watts)               | 16W              |
| IP Rating                  | IP65             |
| Light Source               | LED built in     |
| Dimmable                   | No               |
| F Mark                     | F                |
|                            |                  |
| Fitting                    |                  |
| Input Type                 | Constant Current |
| Input Current              | 500mA            |
| Voltage                    | 30V              |
| Power(Watts)               | 15W              |
| IP Rating                  | IP65             |
| Light Source               | LED built in     |
| LED Type                   | SMD 2835         |
| LED Brand                  | Epistar          |
| LED Number                 | 81               |
| F Mark                     | F                |
|                            |                  |
| Gear                       |                  |
| Gear Type                  | Led Driver       |
|                            |                  |

| Input Voltage  | 220-240V                            |
|--|-------------------------------------|
| 50 Hz  | Yes                                 |
| 60 Hz  | Yes                                 |
| Power(Watts)   | 8,5-16W                             |
| Power Factor   | 0,9                                 |
| Constant Current   | Yes                                 |
| 500mA  | 19-32V                              |
| IP Rating  | IP20                                |
| Safety Class   |                                     |
| Dimmable   | No                                  |
| Housing Material   | Plastic                             |
| Output Terminal  | Connector                           |
| Brand  | Eaglerise                           |
|  |                                     |
| Ilumination Data   |                                     |
|  |                                     |
|  |                                     |
| Colour Temperature   | 3000K                               |
| Colour Temperature  Lumen Output   | 3000K<br>960lm                      |
|  |                                     |
| Lumen Output   | 960lm                               |
| Lumen Output Light Efficiency  | 960lm<br>60lm/W                     |
| Lumen Output Light Efficiency CRI  | 960lm<br>60lm/W                     |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  | 960lm<br>60lm/W                     |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  | 960lm<br>60lm/W                     |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  | 960lm<br>60lm/W                     |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  | 960lm 60lm/W 80                     |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  | 960lm 60lm/VV 80 27cm               |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width                                     | 960lm 60lm/W 80 27cm 27cm           |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height                         | 960lm 60lm/W 80 27cm 27cm 8cm       |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight             | 960lm 60lm/W 80 27cm 27cm 8cm 0,9Kg |
| Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton | 960lm 60lm/W 80 27cm 27cm 8cm 0,9Kg |



#### Certification & Warranty

| Warranty       | 2 Years |
|----------------|---------|
| Weee Directive | Yes     |

# switch to one light!

